

SAFETY DATA SHEET



Version 16.1 replaces Version 15.1
Revision date: 01.04.2016
According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product identifier:** SPOTCHECK® SKC-S - aerosol
- 1.2 Relevant identified uses of the mixture and uses advised against:**
Relevant identified uses: Solvent cleaner used in penetrant inspection.
Uses advised against: This product is not recommended for any use other than the identified uses above.
- 1.3 Details of the supplier of the safety data sheet**
Manufacturer: Magnaflux® (A Division of ITW Ltd)
Address: Faraday Road, South Dorcan Industrial Estate, Swindon, UK
Postcode: SN3 5HE
Telephone/fax number: Telephone: +44 (0)1793 524566
Fax: +44 (0)1793 490459
Web: www.eu.magnaflux.com
Email address of competent person responsible for SDS: datasheets@magnaflux.co.uk
National contact: None appointed.
- 1.4 Emergency telephone number:** T: +44 (0)1793 524566 (office hours)
Opening hours: Office hours (GMT) Monday - Thursday 8am - 5pm, Friday 8am - 4pm
Other comments: Emergency telephone service is provided in English only.

SECTION 2

HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
Classification according to Regulation (EC) No 1272/2008 (CLP): **Physical and Chemical Hazard:** Aerosol 1 H222, H229
Health Hazard: Skin Irrit. 2 H315
STOT SE 3 H336
Environmental Hazard: Aquatic Chronic 2 H411
No other information.
- Additional information**

For full text of hazard statements and EU hazard statements see SECTION 16.

- 2.2 Label Elements:**
Labelling according to regulation (EC) No 1272/2008 [CLP]



Signal Word:

DANGER

SAFETY DATA SHEET

Hazard Statement(s):

H222: Extremely flammable aerosol.
 H229: Pressurised container: may burst if heated.
 H315: Causes skin irritation
 H336: May cause drowsiness or dizziness
 H411: Toxic to aquatic life with long lasting effects

Precautionary Statement(s):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211: Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn even after use.
 P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P501: Dispose of contents/container to hazardous waste or special collection point.
 P271: Use only outdoors or in a well ventilated area.
 P302+352: IF ON SKIN: Wash with soap and water
 P264: Wash thoroughly after handling.
 P362+P364: Take off contaminated clothing and wash it before reuse.

Supplementary Precautionary Statement(s):

None

Supplementary Hazard Information (EU)

Hazard Determining Component(s)

Hydrocarbons, C7 – C9, isoalkanes

2.3

Other hazards:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Vapours can form explosive mixtures with air.

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Hydrocarbons, C7- C9, isoalkanes		921-728-3	01-2119471305-42	60 -100	Flam. Liq 2: H225 Skin Irrit. 2: H315 STOT SE3: H336 Asp. Tox. 1: H304 (note1) Aquatic Chronic 2: H411	No other information
Hydrocarbons, C3-4-rich petroleum distillate petroleum gas (1,3 butadiene < 0.1%)	68512-91-4	270-990-9	(note2)	10-30	Press. Gas H280 Flam. Gas 1 H220	(note3)
1. Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. 2. Exempted from the obligation to register in accordance with art.2(7)(a) of REACH Regulation No 1907/2006 3. Not classified as carcinogen, less than 0.1% w/w 1,3 butadiene (EINECS no 203-450-8)						

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

*See Section 16 for hazard statement(s) text in full.

SAFETY DATA SHEET

SECTION 4

FIRST AID MEASURES

- 4.1 Description of first aid measures:**
- General notes:** If symptoms persist, seek medical attention. Show this safety data sheet to the doctor in attendance.
- Following inhalation:** Remove to fresh air. Keep at rest. If not breathing give artificial respiration. Seek prompt medical attention if discomfort persists.
- Following skin contact:** Flush with water, use soap if available. Contaminated clothing should be washed before re-use. Seek medical attention if irritation persists.
- Following eye contact:** Flush eyes with large amounts of water for at least 15 minutes with eyelids held open. Seek medical attention if irritation persists.
- Following ingestion:** Unlikely route of exposure. Rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach contents don't enter the lungs. Never give anything by mouth to an unconscious person. Seek medical attention immediately.
- Self-protection of the first aider:** No action shall be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective equipment.
- 4.2 Most important symptoms, both acute and delayed:**
Prolonged skin contact may cause redness and irritation.
In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.
Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation. Avoid vomiting and normal rinse of stomach because of risk of aspiration. May cause discomfort to the eyes. Symptoms: redness and pain.
- 4.3 Indication of any immediate medical attention and special treatment needed:**
None known.

SECTION 5

FIREFIGHTING MEASURES

- 5.1 Extinguishing media:**
Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water fog or spray.
- 5.2 Unsuitable extinguishing media:** Do not use water jet.
Special hazards arising from the substance or mixture: Evacuate immediate area. Shut off 'fuel' to fire. If possible keep unaffected containers cool with water spray.
Aerosols may explode in a fire.
Aerosol contents are extremely flammable.
Hazardous combustion products: Smoke, soot and oxides of carbon. Burning vapour may give off toxic fumes.
- 5.3 Advice for fire-fighter:**
Warn firefighters that aerosols are involved. Self contained breathing apparatus and full protective clothing must be worn. Water spray should be used to cool containers. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SAFETY DATA SHEET

SECTION 6

ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:**
Suitable protective equipment (see Section 8) should be worn to prevent any contamination of skin, eyes and personal clothing.
- For non-emergency personnel:** Remove ignition sources. Avoid breathing vapours, mist or gas.
- For emergency responders:** Remove ignition sources. Avoid breathing vapours, mist or gas. Keep unnecessary people at a safe distance.
- 6.2 Environmental precautions:**
Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs.
- 6.3 Methods and material for containment and cleaning up:**
Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge.
Avoid breathing vapours. Ventilate surrounding area.
- For containment:** Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for disposal.
Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national regulations.
- For cleaning up:** Do not flush away residues with water.
- Other information:** No other information.
- 6.4 Reference to other sections:**
For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7

HANDLING & STORAGE

- 7.1 Precautions for safer handling:**
- Protective Measures:** Wear suitable protective clothing such as chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when in use.
Avoid contact with skin and eyes. Do not breathe product spray or mist. Risk of vapour concentration in low areas.
- Measures to prevent fire:** Aerosol contents are highly flammable and volatile. Keep away from sources of ignition – no smoking.
Take measures to prevent the build-up of electrostatic charge.
Equipment should be earthed. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools.
Wash thoroughly after handling.
- Advice on general occupational hygiene:**

SAFETY DATA SHEET

7.2	Conditions for safe storage, including any incompatibilities: Technical measures and storage conditions: Packaging materials:	Store in a cool dry area away from heat and sources of ignition. Store in original container.
	Requirements for storage rooms and vessels:	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Recommended storage temperature 10 °C to 30 °C.
	Further information on storage conditions:	Rotate stock and check regularly for damaged items.
7.3	Specific end use(s): Recommendations:	Use only for Non Destructive Testing (NDT) applications.
	Industrial sector specific solutions:	See product data sheet for further information.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 **Control parameters:**
Occupational exposure limit values:
 Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

Ingredient name	Country	Limit value - 8 hours		Limit value - short term	
		ppm	mg /m ³	ppm	mg /m ³
Hydrocarbons, C7 – C9, isoalkanes	UK	241	1200		

Data obtained from GESTIS International Limit Values, EH40, supplier's SDS

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) - Hydrocarbons, C7 – C9, isoalkanes

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	2035 mg/m ³
Worker	Dermal	Long term	Systemic	773 mg/kg bw/day

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC) - Hydrocarbons, C7 – C9, isoalkanes

Water - Fresh Water	No data available: testing technically not feasible
Water - Marine Water	No data available: testing technically not feasible
Water - Intermittent release	No data available: testing technically not feasible
Sediment - Fresh water	No data available: testing technically not feasible
Sediment - Marine water	No data available: testing technically not feasible
Soil	No data available: testing technically not feasible
Sewage Treatment plant	No data available: testing technically not feasible

SAFETY DATA SHEET

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded

Personal protection equipment:

Eye and face protection:

Safety glasses with side-shields conforming to EN166.

Skin protection - hand:

Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for **isoparaffins**, if hand exposure is unavoidable. Protective gloves made of **nitrile rubber** are suitable, although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to EN374.

Skin protection – other:

Consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific workplace.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Filter type A. (EN 136, 140, 405, 149, 143) For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under CEN standards.

Thermal hazards:

Not applicable.

Environmental exposure controls:

Avoid any release to the environment.

SECTION 9

PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Aerosol containing mobile clear liquid.

Odour:

Mild hydrocarbon.

Odour threshold:

No data available.

pH:

Neutral.

Melting point/freezing point:

No data available.

Initial boiling point and boiling range:

113 – 143 °C.

Flash point (PMCC):

-40 °C (aerosol propellant).

Evaporation rate (BuAc = 100):

155.

Flammability (solid, gas) (Limits in air):

No data available.

Upper/lower flammability or explosive limits:

0.7 – 6.0% (Vol%)

SAFETY DATA SHEET

Vapour pressure:	1.627 kPa @ 20 °C.
Vapour density (Air = 1):	> 1.
Relative density:	0.72 g/cm ³ .
Solubility:	Insoluble.
Partition coefficient: n-octanol/water:	No data available.
Auto-ignition temperature:	> 200 °C.
Decomposition temperature:	No data available.
Viscosity (ASTM D445):	0.86 mm ² /s @ 25 °C.
Explosive properties:	Under normal conditions no danger of explosion.
Oxidising properties:	No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information:
No other information.

SECTION 10 STABILITY & REACTIVITY

10.1	Reactivity:	No specific reactivity hazards associated with this product.
10.2	Chemical stability	Stable under normal conditions of use and applications.
10.3	Possibility of hazardous reactions:	No data available.
10.4	Conditions to avoid:	Keep away from sources of ignition, hot surfaces and direct sun light.
10.5	Incompatible materials:	Strong oxidising agents.
10.6	Hazardous decomposition materials:	None under normal conditions of use. Smoke, soot and oxides of carbon on combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral:	Based on the available data, the classification criteria are not met.
Acute toxicity – dermal:	Based on the available data, the classification criteria are not met.
Acute toxicity – inhalation:	Based on the available data, the classification criteria are not met.
Skin corrosion/irritation:	Skin Irrit. 2 H315: Causes skin irritation.
Serious eye damage/irritation:	Based on the available data, the classification criteria are not met.
Respiratory sensitisation:	Data lacking.
Skin sensitisation:	Based on the available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on the available data, the classification criteria are not met.
Carcinogenicity:	Data lacking.
Reproductive toxicity:	Based on the available data, the classification criteria are not met.

SAFETY DATA SHEET

STOT single exposure: STOT Single Exp. 3 H336: May cause drowsiness or dizziness.
Affected organs: central nervous system
Route of exposure: inhalation

STOT repeated exposure: Based on the available data, the classification criteria are not met.

Aspiration hazard: Mixtures from Aerosol Dispensers - need not be classified as Asp. Tox. 1 - H304 as the aerosol spray is fine and a pool of product may not be formed in the mouth.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: Vapour concentrations above the recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects.

Ingestion: Not a likely route of exposure. However, harmful: May cause lung damage if swallowed. Ingestion may cause irritation of the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary edema.

Eye contact: May cause redness and pain.

Skin contact: Frequent or prolonged contact with the product may produce irritation and/or skin dryness and cracking. Product will have a de-fatting effect on the skin.

Toxicity Test Results: based on data for component materials, where available.

Hydrocarbons, C7 – C9, isoalkanes

Acute Toxicity – oral	LD50 (rat)	> 5000 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 2000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	21 mg/l (4 h; vapour)

Other Information: No other information.

SECTION 12 ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Hydrocarbons, C7 – C9, isoalkanes

Fish	Oncorhynchus mykiss	LL50	96h	18.4 mg/l
Aquatic Invertebrates	Daphnia magna	EL50	48h	2.4 mg/l
Aquatic Plants	Pseudokirchneriella subcapitata	EL50	72h	29 mg/l

12.2 Persistence and degradability: Hydrocarbons, C7 – C9, isoalkanes - Biodegradable.

12.3 Bioaccumulative potential: No data available.

Partition coefficient: n-octanol/water (log Kow): No data available.

Bioconcentration factor (BCF): No data available.

SAFETY DATA SHEET

12.4	Mobility in soil:	The product is immiscible with water and will spread on the water surface. Product is highly volatile - will partition rapidly to air.
12.5	Results of PBT and vPvB assessment:	This mixture does not contain any substances that are assessed to be a PBT or vPvB.
12.6	Other adverse effects:	No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods:	Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.
	Product/packing disposal:	Empty containers may contain residual product and flammable vapours. Do not pierce or burn container, even after use. Do NOT remove labels. Keep away from sources of ignition.
	Waste codes/waste designations according to LoW:	16 05 04* gases in pressure containers containing dangerous substances.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information:	Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation
Sewage disposal – relevant information:	Do not empty down the drain.
Other disposal recommendations:	Use a licensed waste contractor

SECTION 14 TRANSPORT INFORMATION

14.1	UN number:	ADR/RID: UN1950 IMDG: UN1950 IATA: UN1950
14.2	UN proper shipping name:	ADR/RID: AEROSOLS, flammable IMDG: AEROSOLS, flammable IATA: AEROSOLS, flammable
14.3	Transport hazard class(es):	ADR/RID: 2.1 IMDG: 2.1 IATA: 2.1
14.4	Packing group:	ADR/RID: N/A IMDG: N/A IATA: N/A
14.5	Environmental hazards:	ADR/RID: Yes IMDG: Marine Pollutant: Yes IATA: Yes

SAFETY DATA SHEET

- 14.6 Special precautions for user:**
ADR/RID – Tunnel code: (D)
IMDG – Ems: F-D, S-U
IATA/ICAO – PAX: 203
IATA/ICAO – CAO: 203
- 14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:**
Not applicable

SECTION 15 REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**
EU Regulations:
This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.
Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.
Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.
This data sheet is complied according Dir 2013/10/EU, 2008/47/EEC amendment of the aerosol directive 75/324/EEC.
Extra label elements: Pressured container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Mixtures classified as Asp. Tox. 1 H304 need not be labelled when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.
- National regulations (Germany):**
Wassergefährdungsklasse (water hazard class): WGK 2 - Hazard to waters.
TechnischeAnleitungLuft (TA-Luft): Class 5.2.5 Organic Substances, except dusts
- 15.2 Chemical safety assessment:**
No data available

SECTION 16 OTHER INFORMATION

- (i) Indication of changes:**
This safety data sheet has been updated to meet the requirements of Regulation EU No 2015/830 and Regulation (EC) No 1272/2008. Removal of the Classification according to 67/548/EEC as amended & Directive 1999/45/EC. Version 16.1 also updated in Section 8 due to updated safety information.
Vertical lines on the left hand side indicate an amendment from the previous version.
- (ii) Abbreviations and acronyms:**
- | | |
|-----------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road (Accord européen relatif au transport international des marchandises Dangereuses par Route) |
| CAS No. | Chemical Abstracts Service number |
| CEN | European Committee for Standardisation |
| CLP | Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| ECHA | European Chemicals Agency |
| EC50 | Half Maximal Effective Concentration |
| EC number | EINECS and ELINCS number |
| EINECS | European Inventory of Existing Commercial Substances |
| ELINCS | European List of notified Chemical Substances |
| GHS | Globally Harmonized System |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |

SAFETY DATA SHEET

LC50	Lethal Concentration to 50% of a test population
LD50	Lethal Dose to 50% of a test population
MPI	Magnetic Particle Inspection
NDT	Non-Destructive Testing
OEL	Occupational Exposure Limit
PBT	Persistent, Bioaccumulative and Toxic Substance
PMCC	Pensky-Martens closed cup method
PPE	Personal Protection Equipment
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation EC (No) 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail (Reglement International concernant le transport des marchandises Dangereuses par chemin de fer)
SDS	Safety Data Sheet
STOT RE	Specific Target Organ Toxicity, Repeat Exposure
STOT SE	Specific Target Organ Toxicity, Single Exposure
TA-Luft	Technical Instructions on Air Quality Control (Technische Anleitung zur Reinhaltung der Luft)
vPvB	Very Persistent and Very Bioaccumulative
WEL	Workplace Exposure Limit
WGK	German Water Hazard Class (Wassergefährdungsklasse)

(iii) Key literature and sources of data:

- Supplier's safety data sheets for components listed in Section 3.
- European Chemicals Agency, <http://echa.europa.eu/>
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- REACH Directive (EC) 1907/2006.

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Classification according to Regulation (EC) No 1272/2008	Classification procedure
Aerosol. 1: H222, H229	Test Method
Skin Irr. 2: H315	Calculation Method
STOT SE3: H336:	Calculation Method
Aquatic Chronic 2: H411	Calculation Method

(v) Hazard statements (number and full text):

- H220: Extremely flammable gas.
H225: Highly flammable liquid and vapour
H222: Extremely flammable aerosol.
H229: Pressurised container: may explode if heated.
H280: Contains gas under pressure; may burst if heated.
H304: May be fatal if swallowed and enters airways
H315: Causes skin irritation
H336: May cause drowsiness or dizziness
H411: Toxic to aquatic life with long lasting effects

Hazard Class and Category Code (full text):

- Aerosol 1: Aerosol
Aquatic Chronic 2: Hazardous to the aquatic environment
Asp. Tox. 1: Aspiration hazard
Flam. Gas 1: Flammable Gas
Flam. Liq. 2: Flammable liquid
Press. Gas: Gases under pressure
Skin Irrit. 2: Skin corrosion/irritation
STOT SE 3: Specific target organ toxicity - single exposure

SAFETY DATA SHEET

Relevant precautionary statements (number and full text):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well ventilated area.

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+352: IF ON SKIN: Wash with soap and water

P362+P364: Take off contaminated clothing and wash it before reuse.

P264: Wash thoroughly after handling.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi)

Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment.

Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision summary:	Revision Comments	This SDS is valid from the Revision Date. If you require a SDS for the product manufactured before the Revision Date please contact us at datasheets@magnaflux.co.uk .
	Revision Date	01.04.2016
	Version	16.1